Appl. No. 10/604,208
Amd. Dated September 9, 2005
Reply to Office Action Dated March 13th, 2005

Amendments to the Claims:

This listing of the claims will replace all prior versions, and listings, of the claims in the application.

Listing of Claims:

Please amend the claims as follows without prejudice. No new matter has been added by way of these amendments.

1. (Currently Amended)   A method of predicting the operation of a steerable drilling system comprising the steps of:

calculating an ideal reachability ellipse using the

equations:

$$Build = W_{build} * \left[\frac{WOB - meanWOB}{meanWOB}\right] + R_{build} * \left[\frac{ROP - meanROP}{meanROP}\right] + P_{build} * \left[\frac{Pressure - meanPressure}{meanPressure}\right]$$
$$+ F_{build} * \left[\frac{Flow - meanFlow}{meanFlow}\right] + M_{build} * \left[\frac{RPM - meanRPM}{meanRPM}\right] + T_{build} * \left[\frac{Torque - meanTorque}{meanTorque}\right]$$
$$+ I_{build} * \left[\frac{\sin Inc - mean \sin Inc}{mean \sin Inc}\right] + K_D * [BuildDemand\%] + C_{BT} * [TurnDemand\%] + build_{bias}$$

and

$$Turn = W_{turn} * \left[\frac{WOB - meanWOB}{meanWOB}\right] + R_{turn} * \left[\frac{ROP - meanROP}{meanROP}\right] + P_{turn} * \left[\frac{Pressure - meanPressure}{meanPressure}\right]$$
$$+ F_{turn} * \left[\frac{Flow - meanFlow}{meanFlow}\right] + M_{turn} * \left[\frac{RPM - meanRPM}{meanRPM}\right] + T_{turn} * \left[\frac{Torque - meanTorque}{meanTorque}\right] \quad ;$$
$$+ I_{turn} * \left[\frac{\sin Inc - mean \sin Inc}{mean \sin Inc}\right] + K_T * [TurnDemand\%] + C_{TB} * [BuildDemand\%] + turn_{bias}$$

inputting data representative of actual drilling conditions into a parametric model;

Page 2 of 6

calculating predicted build and turn gain, cross-coupling and bias values to derive build and turn responsiveness values attainable under given operating conditions from the parametric model to produce a predicted reachability ellipse;

plotting the predicted reachability ellipse and ideal reachability ellipse on a diagram to compare the predicted build and turn responsiveness to the ideal response for one or more sets of operating conditions.

2.   (Original) A method as claimed in Claim 1, wherein the model data includes data representative of at least one of: weight on bit, rotational speed, rate of progress, torque, pressure, inclination, dip and azimuth of bedding planes or other formation characteristics, hole curvature/gauge or other geometric conditions, bit type and condition, and errors in instrumentation readings.

3.   (Cancelled)

4.   (Original) A method as claimed in Claim 1, wherein an output signal is produced which is used to control a display on which the predicted reachability ellipse diagram is displayed to provide an operator with information for use in controlling the operation of the drilling system.